

H2S 30 low ppb

Electrochemical Gas Sensor for Hydrogen Sulfide

3-electrode sensor for industrial safety and environmental monitoring applications
Class leading stability | Highly selective | Fast response | Very stable baseline







Performance Characteristics	
Measurement Range	0 - 30 ppm
Sensitivity	80 ± 30 nA/ppm
Response Time (T ₉₀)	≤ 30 s at 3 min gas exposure
Baseline (in clean air)	< ± 10 nA
Baseline (in clean air)	< ± 0.1 ppm*
Linearity	< 10% of full scale
Repeatability	< 2%

* at midpoint sensitivity

Operating Conditions	
Temperature Range	-40°C to +40°C
Humidity Range	15% to 90% r.h. non-condensing
Pressure Range	800 - 1200 hPa
Recommended Load Resistor	0 Ohm
Bias Voltage	0 V
Recommended Orientation	sensor front pointing downwards or sideways

Lifetime	
Long Term Output Drift	< 5% per month
Expected Operating Life	> 18 months in air
Recommended Storage conditions	5 - 20°C in sealed container
Warranty	12 months from date of dispatch

Performance and lifetime data are based on conditions at 20°C, 50% r.h. and ambient pressure without NH₃ background concentration.

Available Formats	
Name	Drawing
Part Number Weight	
4S AN233400 ~4.6 g	
7S AN233700 ~6.9 g	
Mini AN233000 ~2.4 g	
Classic 4 pin AN233C00 ~3.1 g	
Classic 8 pin compatible AN233B00 ~3.1 g	
Smart with EPROM AN233800 ~3.1 g	
Other customer specific formats upon request	

IMPORTANT NOTE:

Connection should be made via PCB sockets only. Soldering to pins will render your warranty void.

Intrinsic Safety Data	
Maximum o/c Voltage	< 1.3 V
Maximum s/c Current	< 1.0 A

SAFETY NOTE



This sensor is designed to be used in safety critical applications. To ensure that the sensor and/or instrument in which it is used, are operating properly, it is a requirement that the function of the device is confirmed by exposure to target gas (bump check) before each use of the sensor and/or instrument. In stationary installations this needs to be repeated regularly according to national and local regulations. Failure to carry out such tests may jeopardize the safety of people and property.



H2S 30 low ppb

Electrochemical Gas Sensor for Hydrogen Sulfide

Temperature performance



Temperature Coefficients		
Temperature	Sensitivity	Zero Current
-40 °C	65 %	0.01
-20 °C	85 %	0.01
0 °C	97 %	0.01
20 °C	100 %	0.04
40 °C	97 %	0.07

Temperature data are taken from a typical batch.

Cross Sensitivity & Filter

Gas concentration	Reading after 5 min
Carbon Monoxide 100 ppm	0
Carbon Dioxide 5000 ppm	0
Hydrogen 10000 ppm	0
Isopropanol 600 ppm	0
Methane 2 Vol%	0
Methanol 1000 ppm	0
Nitrogen Dioxide 10 ppm	Yes (tbd)
Sulfur Dioxide 10 ppm	Yes (tbd)
Chemical Filter	None

Signals below baseline are stated as 0

tbd = to be determined


Whilst Sensorix cells are designed to be highly specific to the gas they are intended to measure, they will still respond to some degree to various other gases. The table above is not exclusive and other gases not included in the table may still cause a sensor to react. The cross-sensitivity values quoted are based on tests conducted on a small number of sensors. They are intended to indicate sensor response to gases other than the target gas. Sensors may behave differently with changes in ambient conditions and any batch may show significant variation from the values quoted. Therefore, interfering gases should not be used for calibration.



H2S 30 low ppb

Electrochemical Gas Sensor for Hydrogen Sulfide

Product dimensions



Poisoning

Sensorix cells are designed for operation in a wide range of environments and harsh conditions. However, it is important that exposure to high concentrations of solvent vapors is avoided, both during storage, fitting into instruments, and operation. When using sensors with printed circuit boards (PCBs), degreasing agents should be used before the sensor is fitted.

Recycling

At the end of the product's life, do not dispose of any electronic sensor, component or instrument in the domestic waste, but contact the instrument manufacturer or Sensorix for disposal instructions. Sensorix will take back sensors for professional recycling.

Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continued product improvement Sensorix GmbH reserves the right to make product changes without notice. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale. The products are always subject to a program of improvement and testing which may result in some changes in the characteristics quoted. As the products may be used by the client in circumstances beyond the knowledge and control of Sensorix GmbH, we cannot give any warranty as to the relevance of these particulars to an application. It is the clients' responsibility to carry out the necessary tests to determine the usefulness of the products and to ensure their safety of operation in a particular application.

Performance characteristics on this data sheet outline the performance of newly supplied sensors. Output signal can drift below the lower limit over time.

